

TBS 6991 DVB-S2 Dual Tuner Dual CI PCIe Card

TBS 6991 is a Twin Tuner digital satellite TV card with PCI Express interface for watching and recording digital satellite TV on PC. You may use one tuner to watch one TV channel while using another tuner to record/watch another channel from another transponder/satellite simultaneously. It can be either used for watching Free to Air TV or satellite Pay TV since it's integrated with two CI slots (By inserting the correct CAM and subscription smartcard into the CI slot, encrypted payTV will be available). This device is provided with both Windows BDA driver and Linux driver up to the latest kernel. The unique TBS MCE tool makes it possible to read CAM/Smartcard on Windows7 Media Center, thus your satellite subscription TV can be watched/ recorded on Windows7 Media Center. On Linux platform, you can also watch payTV by using relative software on Linux. TBS 6991 is compatible with Windows7 Media Center, MediaPortal, DVBlind, DVBDream, DVBCViewer, ProgDVB, Skynet, TSreader, XBMC, MythTV, VDR and many other popular softwares.

Descriptions:

TBS 6991 PCI-E DVB-S2 Dual Tuner Dual CI card is the high end satellite TV tuner built with dual Common Interface support, which allows insertion of two CAMs and two smartcards for recording two different payTV channels at the same time. It's good choice especially for IPTV server streaming payTV contents. With use of appropriate software, e.g. MediaPortal and its plugins, you may stream satellite TV contents to your iPhone, iPad or iPod. The built in hardware blindscan capability allows you to scan satellite programs without knowing exact transponder details, this is especially useful for hunting unknown satellite feeds.

Main Features:

- Watch Satellite TV & Listen to Radio on PC
- DVB-S2/DVB-S SD or HD TV Receiving
- Real Time and Scheduled Program Recording (PVR)
- Time Shifting to Pause Live TV
- Dual Tuner for Recording Two Different Channels/Transponders
- Unicable/One Cable Compatible
- Dual Common Interface Support
- Blindscan
- High Reliability

Applications:

- HTPC
- IPTV Streaming Server

Specifications:

- Receiving Frequency: 950~2150 MHz Tuning Range
- Input Level: -69~-23dBm
- 2x DVB-S2/DVB-S 8PSK QPSK Demodulator
- Symbol Rate:
 - DVB-S QPSK 1~45Msps
 - DVB-S2 QPSK/8PSK 1~45Msps
- Carrier Capture Range: ± 10 MHz
- 8PSK Puncture Codes: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
- QPSK Puncture Codes: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
- Support Data Burst & Tone Burst
- Support DiSEqC2.X and Motor
- Dual CI Slot

Standard Profile TV Card Size: 145x92mm (Length x Height)
TV Card Weight: 133 Gram
Package Gift Box Size: 200x140x50mm (Length x Width x Height)
Package Gift Box Weight: 352 Gram

System Requirements:

Windows 2000/XP/Vista/7 or Linux
DirectX9.0 or later Version
Available PCI Express x1, x4, x8 or x16 Slot
Satellite Dish and LNB

For DVB-S:

1GHz CPU or above
256MB RAM or above
Graphic Card with at least 16MB RAM

For DVB-S2 HDTV:

Dualcore CPU
1GB RAM or above
Graphic Card with at least 64MB RAM

Package Content:

1 x TBS 6991 PCI-E DVB-S2 Dual Tuner Dual CI Card
1 x Remote Control
1 x IR Receiver
1 x Software CD
1x Power Cable (The power cable is not necessary to be plugged in most cases)