

TBS5922 DVB-S2 TV Tuner USB¹

TBS5922 is an USB interface digital satellite external TV Tuner box for watching and recording Free to Air satellite TV on PC. It supports both DVB-S2 and DVB-S programs receiving. It's ready with Windows BDA driver and Linux driver up to the latest kernel 3.X (Tested on Ubuntu, Fedora, Opensuse and other Linux distributions). It's compatible with Windows7 Media Center, MediaPortal, DVblink, DVBDream, DVbViewer, ProgDVB, Skynet, TSreader, XBMC, MythTV,VDR and many other popular DVB softwares.

Descriptions:

TBS5922 USB DVB-S2 TV Tuner box is the successor of QBox 3. It's designed with advanced DVB-S2 RF/Demodulator chipsets and it's built with high quality components. You can use it to watch UK Freesat or any other Free to Air satellite TV programs in your region. The built in hardware blindscan capability allows you to scan satellite programs without knowing exact transponder details, this is especially useful for satellite feed hunting.

Main Features:

- Watch Satellite TV & listen to radio on PC
- DVB-S2/DVB-S SD or HD TV receiving
- Broadband Internet via satellite *
- High-speed data download via satellite *
- Real Time and scheduled Program recording(PVR)
- Time shifting to pause live TV
- Unicable/one cable compatible
- Blindscan
- High reliability

*Depends on service provider.

Specifications:

- Receiving frequency: 950~2150 MHz tuning range
- Input level: -69~-23dBm
- DVB-S2/DVB-S 8PSK QPSK demodulator
- Symbol rate:
 - DVB-S QPSK 1~45Msps
 - DVB-S2 QPSK/8PSK 1~45Msps
- Carrier capture range: ± 10 MHz
- DVB-S2 CCM
 - QPSK+1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
 - 8PSK+3/5, 2/3, 3/4, 5/6, 8/9, 9/10
- DVB-S
 - QPSK+1/2, 2/3, 3/4, 5/6, 7/8
- Support data burst & tone burst
- Support DiSEqC2.X and motor

¹TBS5922 is discontinued, more information about the latest product of this series can be found on www.tbsdtv.com

System Requirements:

Windows 2000/XP/Vista/7 or Linux

DirectX9.0 or later version

Available USB2.0 Port

Satellite Dish and LNB

For DVB-S:

1GHz CPU or above

256MB RAM or above

Graphic Card with at least 16MB RAM

For DVB-S2 HDTV:

Dualcore CPU

1GB RAM or above

Graphic card with at least 64MB RAM

Package Contents:

1 x TBS5922 USB DVB-S2 TV Tuner Box

1 x remote control

1 x Power adapter

1 x USB cable

1 x Software CD