

TBS6991SE DVB-S2 Dual Tuner Dual CI PCIe Card

Descriptions:

TBS6991SE DVB-S2 Dual Tuner Dual CI PCIe Card is a twin tuner digital satellite TV for watching or recording two different channels from two different frequencies simultaneously. You can use one tuner to watch TV channel while using another tuner to record/watch another channel from another transponder/ satellite at same time.

TBS6991SE DVB-S2 Dual Tuner Dual CI PCIe Card is not only available to access Free Air TV but also can watch satellite Pay TV since it's integrated with two CI slots. Inserting the correct CAM and subscription smartcard into the CI slot makes it possible to watch encrypted pay TV.

This device is provided with both Windows BDA driver and Linux driver up to the latest kernel. The unique TBS MCE tool makes it possible to read CAM/Smartcard on Windows7 Media Center, thus your satellite subscription TV can be watched/ recorded on Windows7 Media Center. On Linux platform, you can also watch PayTV by using relative software on Linux.

TBS6991SE DVB-S2 Dual Tuner Dual CI PCIe Card is compatible with Windows7 Media Center, MediaPortal, DVblink, DVBDream, DVBViewer, ProgDVB, Skynet, TSreader, XBMC, MythTV, VDR and many other popular software.

Main Features:

- Watch satellite TV & listen to radio on PC
- DVB-S2/DVB-S SD or HD TV receiving
- Real time and scheduled program recording (PVR)
- Dual tuner for watching two different channels/transponders
- Dual tuner for recording two different channels/transponders
- Dual CI slots for insert CAM and smart card to decrypt the encrypted Pay TV channels
- Time shifting to pause live TV
- Unicable/one Cable compatible
- Dual common Interface Support
- Blindscan support
- High reliability

Specifications:

- Receiving frequency: 950~2150 MHz tuning range
- Input level: -69~-23dBm
- 2x DVB-S2/DVB-S 8PSK QPSK demodulator
- Symbol rate:
 - DVB-S QPSK 1~45Msps
 - DVB-S2 QPSK/8PSK 1~45Msps
- Carrier capture range: ± 10 MHz
 - DVB-S2 CCM
 - QPSK+1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
 - 8PSK+3/5, 2/3, 3/4, 5/6, 8/9, 9/10
 - DVB-S
 - QPSK+1/2, 2/3, 3/4, 5/6, 7/8
- Support data burst & tone burst

Support DiSEqC2.X and motor
Dual CI Slot
Standard profile TV card size: 145x92mm (Length x Height)
TV card weight: 133 Gram
Package gift box size: 200x140x50mm (Length x Width x Height)
Package gift box weight: 352 Gram

System Requirements:

Windows 2000/XP/Vista/7/8/10 or Linux
DirectX9.0 or later Version
Available PCI Express x1,x4, x8 or x16 slot
Satellite Dish and LNB

For DVB-S:

1GHz CPU or above
256MB RAM or above
Graphic card with at least 16MB RAM

For DVB-S2 HDTV:

Dualcore CPU
1GB RAM or above
Graphic card with at least 64MB RAM

Package Contents:

1 x TBS6991SE DVB-S2 dual tuner dual CI PCIe card
1 x Remote control
1 x IR receiver
1 x Software CD
1 x Power cable